

JXF Metal Enclosure

Standard: EN60529

JXF Metal Enclosure provide

- Control, monitoring, measurement and protection for the electric power loops and main power controlling equipment.

Function

Order Information

Type	Thickness of iron charge(mm)	Dimension(mm)								Lock	Reference
		Overall			Installation		Mounting				
		H	W	D	H1	B1	H6	B6	Thick		
JXF—2520 / 14 IP43 Improved	1.0	250	200	140	290	150	170	158	1.0	1	JXF252014B
JXF—3025 / 14 IP43 Improved	1.0	300	250	140	340	200	220	208	1.0	1	JXF302514B
JXF—3025 / 18 IP43 Improved	1.0	300	250	180	340	200	220	208	1.0	1	JXF302518B
JXF—3030 / 14 IP43 Improved	1.0	300	300	140	340	250	220	258	1.0	1	JXF303014B
JXF—3030 / 18 IP43 Improved	1.0	300	300	200	340	250	220	258	1.0	1	JXF303018B
JXF—4030 / 14 IP43 Improved	1.0	400	300	140	440	250	320	258	1.0	1	JXF403014B
JXF—4030 / 20 IP43 Improved	1.0	400	300	200	440	250	320	258	1.0	1	JXF403020B
JXF—5040 / 14 IP43 Improved	1.0	500	400	250	540	350	420	358	1.0	2	JXF504014B
JXF—5040 / 20 IP43 Improved	1.0	500	400	140	540	350	420	358	1.0	2	JXF504020B
JXF—5040 / 25 IP43 Improved	1.0	500	400	200	540	350	420	358	1.0	2	JXF504025B
JXF—6040 / 14 IP43 Improved	1.2	600	400	250	640	350	520	358	1.2	2	JXF604014B
JXF—6040 / 20 IP43 Improved	1.2	600	400	140	640	350	520	358	1.2	2	JXF604020B
JXF—6040 / 25 IP43 Improved	1.2	600	400	200	640	350	520	358	1.2	2	JXF604025B
JXF—6050 / 14 IP43 Improved	1.2	600	500	250	640	450	520	458	1.2	2	JXF605014B
JXF—6050 / 20 IP43 Improved	1.2	600	500	140	640	450	520	458	1.2	2	JXF605020B
JXF—6050 / 25 IP43 Improved	1.2	600	500	160	640	450	520	458	1.2	2	JXF605025B
JXF—7050 / 16 IP43 Improved	1.2	700	500	200	740	450	620	458	1.2	2	JXF705016B
JXF—7050 / 20 IP43 Improved	1.2	700	500	250	740	450	620	458	1.2	2	JXF705020B
JXF—7050 / 25 IP43 Improved	1.2	700	500	200	740	450	620	458	1.2	2	JXF705025B
JXF—8060 / 20 IP43 Improved	1.5	800	600	250	840	550	720	558	1.5	2	JXF806020B
JXF—8060 / 25 IP43 Improved	1.5	800	600	250	840	550	720	558	1.5	2	JXF806025B
JXF—10080 / 20 IP43 Improved	1.5	1000	800	200	1040	750	920	758	1.5	2	JXF1008020B
JXF—10080 / 25 IP43 Improved	1.5	1000	800	250	1040	750	920	758	1.5	2	JXF1008025B
JXF—10080 / 30 IP43 Improved	1.5	1000	800	300	1040	750	920	758	1.5	2	JXF1008030B
JXF—2520/14 IP54	1.2	250	200	140	320	150	215	148	2.0		JXF252014Q
JXF—3025/14 IP54	1.2	300	250	140	370	200	265	198	2.0	1	JXF302514Q
JXF—3025/18 IP54	1.2	300	250	370	200	265	265	198	2.0	1	JXF302518Q
JXF—3030/14 IP54	1.2	300	300	370	250	265	265	248	2.0	1	JXF303014Q
JXF—3030/1 8 IP54	1.2	300	300	370	250	265	265	248	2.0	1	JXF30301 8Q
JXF—4030/14 IP54	1.2	400	300	470	250	365	365	248	2.0	1	JXF403014Q
JXF—4030/20 IP54	1.2	400	300	470	250	365	365	248	2.0	1	JXF403020Q
JXF—5040/14 IP54	1.2	500	400	570	350	465	465	348	2.0	2	JXF504014Q
JXF—5040/20 IP54	1.2	500	400	570	350	465	465	348	2.0	2	JXF504020Q
JXF—5040/25 IP54	1.2	500	400	570	350	465	465	348	2.0	2	JXF504025Q
JXF—6040/14 IP54	1.5	600	400	670	350	565	565	348	2.0	2	JXF604014Q
JXF—6040/20 IP54	1.5	600	400	670	350	565	565	348	2.0	2	JXF604020Q
JXF—6040/25 IP54	1.5	600	400	670	350	565	565	348	2.0	2	JXF604025Q
JXF—6050/14 IP54	1.5	600	500	670	450	565	565	448	2.0	2	JXF605014Q
JXF—6050/20 IP54	1.5	600	500	670	450	565	565	448	2.0	2	JXF605020Q
JXF—6050/25 IP54	1.5	600	500	670	450	565	565	448	2.0	2	JXF605025Q
JXF—7050/1 6 IP54	1.5	700	500	770	450	665	665	448	2.0	2	JXF705016Q
JXF—7050/20 IP54	1.5	700	500	770	450	665	665	448	2.0	2	JXF705020Q
JXF—7050/25 IP54	1.5	700	500	770	450	665	665	448	2.0	2	JXF705025Q
JXF—8060/20 IP54	1.5	800	600	870	550	765	765	548	2.0	2	JXF806020Q
JXF—8060/25 IP54	1.5	800	600	870	550	765	765	548	2.0	2	JXF806025Q
JXF—10080/20 IP54	1.5	1000	800	1070	750	965	965	748	2.0	2	JXF1008020Q
JXF—10080/25 IP54	1.5	1000	800	1070	750	965	965	748	2.0	2	JXF1008025Q
JXF—10080/30 IP54	1.5	1000	800	1070	750	965	965	748	2.0	2	JXF1008030Q



Technical Data

Type	JXF IP43 Improved	IP54
Protection grade	IP43	IP54
Standard:	EN60529	EN60529
Certificate	CE	CE
Rated voltage	220/400V	220/400V
Rated insulated voltage	660V	660V
Rated operating current	400A	400A
Withstand current	15kA	15kA
Sheet thickness	1.0~1.5mm	1.2~1.5mm
Mounting plate thickness	1.0~1.5mm	2.0mm
Hinge	Enhanced	Enhanced
Sealing rubber gasket	Black rubber gasket	Black rubber gasket
Cable gland	bottom only	bottom only

Overall Dimensions

